






















Pixel	
ZOOM	
ROM	
RAM	
S	
	Progressive
  	  
 	
Commande d'activation/ Désactivation de l'éclairage	hriorité oom/U an el/omart
Nombre d'éclairages	


Objectif


Distance focale	,8 mm à 15 mm								
Ouverture Max.	F ,6 à F ,0								
Champ de vision	?81° à 2,3 ° : 31,92° à 1,3 ° : 63, 1° à 2, 1°								
Zoom Optique	32								
Mise au point	Automatique/semi-automatique/manuel								
Distance focale minimale	3 m à 5,0 m 2,62 pi à 16 0 pieds								
Contrôle de l'iris	Automatique/Manuel								
Distance DORI	<table border="1"> <thead> <tr> <th>Detéction</th> <th>Observation</th> <th>reconnaissance</th> <th>Identification</th> </tr> </thead> <tbody> <tr> <td>2,12 m 6,968 50 ft</td> <td>839 m 2, 52 62 ft</td> <td>25 m 1,39 36 ft</td> <td>212 m 695 5 ft</td> </tr> </tbody> </table>	Detéction	Observation	reconnaissance	Identification	2,12 m 6,968 50 ft	839 m 2, 52 62 ft	25 m 1,39 36 ft	212 m 695 5 ft
	Detéction	Observation	reconnaissance	Identification					
2,12 m 6,968 50 ft	839 m 2, 52 62 ft	25 m 1,39 36 ft	212 m 695 5 ft						

P

Angle de Panoramique/ Inclinaison	Panoramique : de 0° à 360° sans fin Inclinaison : de -15 ° à 90 °, inversion automatique à 180 °
Contrôle de Vitesse Manuel	Panoramique : 0,1 /s à 300 /s Inclinaison : 0,1°/s – 200°/s
Preset Speed	
Preset	
Tour	
Pattern	5
Scan	5
Power-off Memory	Yes
Idle Motion	
PTZ Protocol	


Intelligence

Smart Capture	 image capture.
---------------	--

IVS (WDR)	
	
Auto Tracking	
SMD PLUS	

S	
Video Compression	
Streaming Capability	
Resolution	
Video Frame Rate	
Bit Rate Control	
Video Bit Rate	
Day/Night	
BLC	
WDR	
HLC	
White Balance	
Gain Control	
Noise Reduction	
Motion Detection	
Region of Interest (RoI)	
Image Stabilization	
Defog	
Digital Zoom	
Image Rotation	
Privacy Masking	
S/N Ratio	

Audio

Audio Compression	
	
Network Port	
Network Protocol	
Interoperability	
Streaming Method	

User/Host	20 (total bandwidth: 64 M)
Storage	FTP; Micro SD card (512 GB); NAS
Browser	IE: IE7 and later Chrome: 42 and earlier Firefox: 52 and earlier Safari
Management Software	Smart PSS; DSS; DMSS; Easy4ip; IVSS
Mobile Client	iOS; Android

Certification

Certifications	CE-LVD: EN 62368-1 CE-EMC: EN55032:2015/EN61000-3-2; 2019/EN61000-3-3; 2013+A1: 2019 /EN50130-4: 2011/A1: 2014/EN55024: 2010/A1: 2015/EN55035: 2017 FCC: CFR 47 FCC Part15, Subpart B UL: UL60950-1+CAN/CSA C22.2, No.60950-1
----------------	---

Port

Two-way Audio	Yes
Alarm Linkage	Capture; preset; tour; pattern; recording; triggering on-off value output; audio; sending email
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection; power exception detection
Alarm I/O	2/1
Audio I/O	1/1

Power

Power Supply	24 VDC, 2.5 A (± 25%) PoE+ (802.3at)
Power Consumption	Basic: 13 W Max.: 22 W (illuminator + PTZ working)

Environment

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Operating Humidity	≤ 95%
Protection	IP67; IK10; TVS 6000 V lightning proof; surge protection; voltage transient protection

Structure

Product Dimensions	331.9 mm × Φ190.4 mm (13.07" × Φ7.50")
Net Weight	4.7 kg (10.36 lb)
Gross Weight	8 kg (17.64 lb)

Ordering Information

Type	Model	Description
4M WizSense Network PTZ Camera	DH-SD5A432XB-HNR	4MP 32x Starlight IR WizSense Network PTZ Camera
	SD5A432XB-HNR	4MP 32x Starlight IR WizSense Network PTZ Camera
Accessories	PFB305W	Wall Mount Bracket
	DC24V/2.5A	Power Adapter
	PFA111	Mount Adapter
	PFA140	Power Box
	PFB300C	Ceiling Mount Bracket
	PFA120	Junction Box
	PFA150	Pole Mount Bracket
	PFA151	Corner Mount Bracket
	PFB303S	Parapet Mount Bracket

Accessories

Included:



PFB305W
Wall Mount Bracket



DC24V/2.5A
Power Adapter

Optional:



PFA111
Mount Adapter



PFA140
Power Box



PFB300C
Ceiling Mount Bracket



PFA120
Junction Box









PFA150
Pole Mount Bracket



PFA151
Corner Mount Bracket



PFB303S
Parapet Mount Bracket

Wall Mount PFB305W+PFA120 	Ceiling Mount PFA111+PFB300C 	Ceiling Mount PFA111+PFB301C 
Pole Mount(Vertical) PFB305W+PFA150 	Corner Mount PFB305W+PFA151 	Pole Mount(Horizontal) PFA111+PFB300C+PFA150 

Dimensions (mm[inch])

