

DH_XVR5x16-X_MultiLang_ V4.001.0000000.9.R.200918

Release Notes

ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD.

Copyright

© 2020 ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD. All rights reserved.

This document cannot be copied, transferred, distributed, or saved in any form without the prior written permission of Zhejiang Dahua Vision Technology Co., LTD (hereinafter referred to as "Dahua").

The products described in this document may contain the software that belongs to Dahua or the third party. Without the prior written approval of the corresponding party, any person cannot (including but not limited to) copy, distribute, amend, abstract, reverse compile, decode, reverse engineer, rent, transfer, sublicense the software.

Trademarks



of Dahua.

All other company names and trademarks mentioned herein are the properties of their respective owners.

Disclaimer

- These release notes are for reference only, and the actual product shall prevail.
- Succeeding products and release notes are subject to change without notice.
- If there is any uncertainty or controversy, please refer to our final explanation.

Table of Contents

Legal Information	
Release Notes	1
1.1 Overview	1
1.2 Basic Functions and Applications	1
1.3 New Features	1
1.4 Instructions for New Features	2
1.4.1 5M Camera Access	2
1.4.2 Items added in disarming: Siren and warning light	2
1.4.3 New languages supported: Traditional Chinese and Japanese	3
1.4.4 Quick Operations on Main Menu	4
1.5 Fixed Bugs	
1.6 Compatibility	5
1.7 Software Environment	5
1.8 Pending Issues	5
1.9 Upgrade Guide	

1.1 Overview

Item	Description		
Product name	DIGITAL VIDEO RECORDER		
Version	V4.001.0000000.9		
	DH-XVR5108H-4KL-X-8P;DH-XVR5208AN-4KL-X		
	-8P;DH-XVR4232AN-X;DH-XVR5108H-4KL-X;DH-XVR5108HS-4KL-X;DH-XVR5116		
Product model	H-X;DH-XVR5116HE-X;DH-XVR5116HS-X;DH-XVR5208AN-4KL-X;DH-XVR5216A-X;		
Product model	DH-XVR5216AN-X;DH-XVR7104E-4KL-B-X;DH-XVR7104E-4KL-X;DH-XVR7108E-4		
	KL-B-X;DH-XVR7108E-4KL-X;DH-XVR7108HE-4KL-X;DH-XVR7208A-4KL-X;DH-XV		
	R1B16H;DH-XVR5416L-X;DH-XVR5816S-X;DH-XVR5216AN-X-16P;		
Software package	DH_XVR5x16-X_MultiLang_V4.001.0000000.9.R.200918.zip		
information			
OS requirement	None		
Release date	2020-09-18		

1.2 Basic Functions and Applications

This series of product is to work with the camera and HDD to monitor the specified position in the indoor environments. It can monitor, playback and support remote surveillance, once the device is connected to the network. It supports cellphone monitor from anywhere anytime with the Internet.

This series of product supports five camera signals (CVI, AHD, TVI, CVBS, and IPC) and can connect to the popular signal types on today's market. It can use the original coaxial cable and support network cable too. It is suitable to upgrade the current system; at the same time, it can meet the expansible requirements of new projects.

CVI product has entered the H.265 era. With the lower bit stream, and higher compression technology, it can reduce storage space and network transmission data.

1.3 New Features

For new H.265 series products with new software security baseline, the following features are added:

No.	Feature	Description
1	Items added in disarming:	Supports one-click arming and disarming with all linkage actions;
I	Siren and warning light	added siren and warning light linkage actions.
2	5M camera access	Supports access of 2880 x 1620 resolution 5M camera.
3	Supports importing custom voice on DMSS app to HDCIV camera	Custom voice on DMSS app can be imported from XVR to HDCVI camera.

Features might vary from different models, and the actual product shall prevail.

1.4 Instructions for New Features

1.4.1 5M Camera Access

4

Supports access of 2880 x 1620 resolution 5M camera, provides image effect more real and clear displayed on 16:9 monitors.

CAMERA						_ ×
Image	Audio/Video	Snapshot	Over	lay		
> Encode	Channel	1				
PTZ	Main Stream			Sub Stream		
Channel Type	Smart Codec			Video		
	Туре	General		Stream Type	Sub Stream 1	-
	Compression	H.265		Compression	H.265	-
	Resolution	2880x1620(5MP)	•	Resolution	352x288(CIF)	-
	Frame Rate(FPS)	25		Frame Rate(FPS)	15	-
	Bit Rate Type	CBR		Bit Rate Type	CBR	~
	Quality			Quality		-
	I Frame Interval	1sec.		I Frame Interval	1sec.	-
	Bit Rate(Kb/S)	4096		Bit Rate(Kb/S)	320	-
	Reference Bit Rate	2560-6144Kb/S		Reference Bit Rate	32-640Kb/S	
	Watermark					
	Watermark String					
	Default				Copy to Refresh	ОК

1.4.2 Items added in disarming: Siren and warning light

Supports one-click arming and disarming with all linkage actions; added siren and warning light linkage actions. You can configure alarm linkages in **Main Menu > ALARM > Disarming**.

ALARM				_ 1	×
Alarm Info	Disarming				
Alarm-in Port	Disarm Alarm Linl	kage Action			
Alarm-out Port		All			
Video Detection		Buzzer			
Exception		Show Message			
Disarming		Alarm-out Port			
		Send Email			
	(Siren			
	Default			Refresh	

1.4.3 New languages supported: Traditional Chinese and

Japanese

This release supports four new languages: Traditional Chinese and Japanese. You can set those languages in start-up wizard or in **SYSTEM** > **General** > **Basic**.

SYSTEM				-	×
> General	Basic	Date&Time	Holiday		
> General	Device Name Device No. Language Video Standard Sync Remote Device Logout Time Navigation Bar	XVR 8 English English 医音中文 Italiano Español(Latinoamérica) 日本語 РУССКИЙ Français	Holiday zone) min. (0-60)		
		Deutsch Português - ·		Refresh	


1.4.4 Quick Operations on Main Menu

Shortcut icons for sub menus (except for SEARCH sub menu) and setting pages on local GUI to quickly jump to other modules: Enter a sub menu or setting page, this document uses BACKUP sub menu as an example. You can find shortcut icons upper in the interface. The icon of the current submenu or setting page displays in highlight and other icons in dim color. When you move mouse pointer to another icon, the icon will display in highlight, and then you can click the icon to enter the submenu or setting page.

The SEARCH sub menu does not support shortcut icons.



ii. Switch icon to turn page: Both local GUI and web support this function.



1.5 Fixed Bugs

N/A

1.6 Compatibility

Current version is V4.001.0000000.9.R

1.7 Software Environment

Platform Model		Version			
	SmartPss	General_SMARTPSS-Win64_ChnEng_IS_V2.003.0000001.0.R.19102			
		8.zip			
		General_SMARTPSS-Win32_ChnEng_IS_V2.003.0000001.0.R.19102			
		8.zip			
	NETKB5000	General_NKB5000_MultiLang_SDA_V3.212.0000000.0.R.191105.BIN			
Baseline	NETKB1000	General_NKB1000_ChnEng_V2.620.0000000.0.R.20180115.zip			
software	DSS	DSS-PRO			
		General_DSS-PRO_Win64_IS_V7.002.0000003.0.R.20191008.exe			
		DSS express			
		General_DSS-Express_win32_IS_V1.000.0000003.1.R.20190817.exe			
	NetSDK	General_NetSDK_Eng_Win32_IS_V3.051.0000006.1.R.191126.7z			
	ConfigTool	General_ConfigTool_ChnEng_V4.011.0000003.6.R.20200114.zip			
Decoder		General_NVD0405DH-4K_Eng_P_V3.200.0002.1.R.20180116.zip			
Player		General_SmartPlayer-Win32_Eng_IS_V4.000.0000001.4.R.191009.zip			
		Android: Gdmss plus 1.10.000			
Cell phone		Iphone: Idmss plus 1.10.000			

1.8 Pending Issues

N/A

1.9 Upgrade Guide

- The upgrade mode includes configtool, web and USB device. Please refer to the upgrade manual for detailed information.
- During the upgrade process, some functions are null, such as record and network preview. After upgrade and reboot process, the device becomes OK.
- The previous device settings remain the same.
- During the upgrade process, do not shut down the device or unplug the power cord. Otherwise, the device may become malfunction and cannot boot up.

ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD.

Address: No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China Postcode: 310053 Tel: +86-571-87688883 Fax: +86-571-87688815 Email: overseas@dahuatech.com Website: www.dahuasecurity.com